



MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: R-PAG SERIES
OTHER/GENERIC NAMES: PAG, POLYALKYLENE GLYCOL REFRIGERATION OIL
PRODUCT USE: Lubricant; Refrigeration Compressor Lubricant
EXIM TRADING LLC 12601 NW 115TH Ave, Unit 111A, Medley, FL, 33178
☎ (305) 884 7882 📠 (305) 884 7883

FOR EMERGENCY

Medical: 1-800-498-5701
Transportation: Chemtrec 1-800-424-9300
OUTSIDE UNITED STATES, CALL COLLECT 1-352-323-3500

2. COMPOSITION / INFORMATION ON INGREDIENTS

Description This product does not contain any substances classified as hazardous to health

Component Name	CAS Number	% (w/w)	OSHA PEL	ACGIH TLV
Polyoxoalkylene glycol ether	---	---	No PEL established	No TL established

Ingredients not precisely identified are proprietary or nonhazardous.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

COLOR: Clear

PHYSICAL FORM: Liquid

ODOR: Odorless

MAJOR HEALTH HAZARDS: EXCESSIVE INHALATION EXPOSURE MAY CAUSE IRRITATION OF RESPIRATORY PASSAGES. MAY BE HARMFUL IF SWALLOWED. INHALATION OR INGESTION MAY CAUSE MUCOUS MEMBRANE IRRITATION

PRECAUTIONARY STATEMENTS: Do not breathe vapor or mist. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Keep container tightly closed. Wash thoroughly after handling. Use only with adequate ventilation.



POTENTIAL HEALTH EFFECTS:

Routes of Exposure

- EYE CONTACT:** Eye contact May cause eye irritation.
- SKIN CONTACT:** Short contact periods with human skin are not usually associated with skin irritation. Repeated and/or prolonged contact may cause irritation. No toxic effects are expected if absorbed through the skin.
- INHALATION:** This material may cause irritation following inhalation. No toxic effects are known to be associated with inhalation of this material.
- INGESTION:** In humans, irritation of the mouth, pharynx, esophagus and stomach can develop following ingestion of this product. May be harmful if swallowed.
- OTHER:** Not listed by ACGIH, IARC, NIOSH, NTP or OSHA.

4. FIRST AID MEASURES

- Skin contact** Wash affected areas thoroughly with soap and water. Wash contaminated clothing before reuse. If redness, itching, or a burning sensation develops, get medical attention.
- Eye contact** Flush with clean, lukewarm water (low pressure) occasionally lifting eyelids for at least 15 minutes. If redness, itching, or a burning sensation develops, have eyes examined and treated by medical personnel.
- Inhalation** Avoid breathing oil mists. Remove to fresh air. Give artificial respiration if not breathing. Oxygen may be given by qualified personnel if breathing is difficult. Get medical attention.
- Ingestion** DO NOT INDUCE VOMITING. Fluid has laxative effect. Give one or two glasses of water to drink and refer to medical personnel. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

- EXTINGUISHING MEDIA:** For small fires: Carbon dioxide (CO₂) Dry chemical, Foam, Water spray.
- FIRE HAZARDS:** LOW FIRE HAZARD - Do not cut, drill, or weld empty containers
- PROTECTIVE EQUIPMENT:** A self contained breathing apparatus and suitable protective clothing must be worn in fire conditions.

6. ACCIDENTAL RELEASE MEASURES

- PERSONAL PRECAUTIONS:** Ensure adequate ventilation of the working area.
- ENVIRONMENTAL PRECAUTIONS:** Do not allow product to enter drains. Prevent further spillage if safe.
- CLEAN UP METHOD:** Absorb with inert, absorbent material and shovel into a chemical waste container. Transfer to suitable, labeled



containers for disposal. Clean spillage area thoroughly with plenty of water containing detergent and flush to a sewer serviced by a permitted wastewater treatment facility.

7. HANDLING AND STORAGE

NORMAL HANDLING:

(Always wear recommended personal protective equipment)

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

STORAGE RECOMMENDATIONS:

This material is hygroscopic. Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labeled containers. Store at a maximum temperature of 40°C

WASTE DISPOSAL METHODS:

This product has been evaluated for RCRA characteristics and does not meet the criteria of a hazardous waste if discarded in its purchased form. Under RCRA, it is the responsibility of the user of the product to determine at the time of disposal, whether the product meets RCRA criteria for hazardous waste. This is because product uses, transformations, mixtures, processes, etc. may render the resulting materials hazardous.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING MEASURES: Ensure adequate ventilation of the working area.

OCCUPATIONAL EXPOSURE CONTROLS: Keep away from food, drink and animal feed.

RESPIRATORY PROTECTION: Normally not necessary. If mist is generated, wear approved organic vapor respirator suitable for oil mist areas with sufficient oxygen.

SKIN/HAND PROTECTION: Normally none required, for direct contact of more than 2 hours, PVC, Viton, or Nitrile gloves are recommended.

EYE PROTECTION: Normally none required, chemical goggles if splashing is likely or high pressure systems are used.

VENTILATION: General ventilation

PROTECTIVE EQUIPMENT: Protect clothing from contact with the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

GENERAL PROPERTIES

DESCRIPTION:	Liquid
COLOR:	Clear
ODOR:	Odorless
FREEZING POINT:	N/A



MSDS R-PAG SERIES

BOILING POINT: >536 °F; >280 °C
VAPOR PRESSURE: N/A @ 20°C
VAPOR DENSITY: No test data available
VOC: Negligible
pH: N/A
SPECIFIC GRAVITY: 0.9968 (H₂O = 1)
EVAPORATION RATE: N/A (H₂O = 1)
SOLUBILITY IN WATER: N/A

SPECIFIC PROPERTIES

Lubrication Properties	OEM Specifications		A-PAG-46	A-PAG-68	A-PAG-100	A-PAG-150
	Ford	GM				
Density g/ml @15°C	0.95 - 1.05	--	0.98	0.98	0.99	0.99
Viscosity @ 40°C	46 min	90-150	46.4	61	99	125
Pour Point °F	-40	-34	-51	-49	-47	-43
Viscosity Index	--	150	186	178	188	189
Water Content, PPM	1,000 max	--	<200	<200	<200	<200
Flash Point °F	392	--	425	437	440	440
TAN# mg KOH/g	--	1.68	0.3	0.3	0.3	0.3
Falex Wear lb at failure	600	926	1,950	1,950	1,950	1,950
FZG Wear Test	--	--	12+	12+	12+	12+
Copper Corrosion, 24hr	--	--	1a	1a	1a	1a

10. STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions.
HAZARDOUS POLYMERIZATION Will not occur
MATERIALS TO AVOID: Strong oxidizing agents, alkali metals.
DECOMPOSITION PRODUCTS: Analogous compounds evolve, carbon monoxide, carbon dioxide, and other undefined fragments.

11. TOXICOLOGICAL INFORMATION

Polyoxoakylene glycol ether LD₅₀: 2,000 mg/kg (oral - rat)

12. ECOLOGICAL INFORMATION

ECOTOXICITY: No data is available on this product

13. DISPOSAL CONSIDERATIONS

GENERAL INFORMATION Dispose of in compliance with all local and national regulations.



CONTAINER DISPOSAL Empty container retains product residue. Observe all hazard precautions. Do not distribute, make available, furnish or reuse empty container except for storage and shipment of original product. Remove all product residues from container and puncture or otherwise destroy empty container before disposal.

14. TRANSPORT INFORMATION

PROPER SHIPPING NAME: Not regulated.
HAZARD CLASS: NA
IDENTIFICATION NUMBER: NA
DOT Emergency Guide #: NA
Reportable Quantity (RQ): NA
International: NA

15. REGULATORY INFORMATION

RISK PHRASES NSH - No Significant Hazard.
OSHA STATUS Non Hazardous under 29 CFR 1910.1200
TSCA STATUS N/A
RCRA STATUS If discarded in its purchased form this product would not be a hazardous waste either by listing or characteristic. However it is the responsibility of the product user to determine at the time of disposal, whether the material being disposed of is a hazardous waste (40 CFR 261.20-24).
CALIFORNIA PROP 65 This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

16. OTHER INFORMATION

	Health Hazard	Flammability	Physical Hazard	Instability
HMIS Classification	1	1	0	

IMPORTANT: The information presented herein, while not guaranteed, was prepared by competent technical personnel and is true and accurate to the best of our knowledge. **NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, SUITABILITY, STABILITY OR OTHERWISE.** The information included herein is not intended to be all-inclusive as to the appropriate manner and/or conditions of use, handling and/or storage. Factors pertaining to certain conditions of storage, handling, or use of this product may involve other or additional safety or performance



MSDS R-PAG SERIES

considerations. While our technical personnel will be happy to respond to questions regarding safe handling and use procedures, safe handling and use remains the responsibility of the customer. No suggestions for use are intended to, and nothing herein shall be construed as a recommendation to, infringe any existing patents or violate any laws, rules, regulations or ordinances of any governmental entity.